

PRODUCT NO. 2347-399120

DOTLUX LED luminaire LUNA IP44 Ø330mm 18W COLORselect



to the product page

- Shadow-free light distribution with very stable PMMA cover IK07
- Constant light output due to large area aluminum core board
- Easy installation, thanks to through-wireable luminaire terminal block
- Sustainable, repairable product design
- The luminaire is suitable for central batteries

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2347-0FW180 2347-1FW180 2347-2FW180
WEIGHT IN KG	0.58
LUMEN PER WATT	121/130/127
POWER CONSUMPTION IN WATTS	18
NET LUMINOUS FLUX IN LUMENS	2180/2340/2290

Dimensions

height: 95mm
diameter: 330mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP44
LIGHT COLOR	multicoloured
INPUT VOLTAGE	186 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	121/130/127
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
INSTALLATION OPENING LENGHT IN MM	0
WARRANTY IN YEARS	5
L80/B10	50000
RATED CURRENT	0,08
SUITABLE FOR SURFACE MOUNTING	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
MATERIAL COVER	Plastic, opal
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK07
WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	18
LAMP TYPE	LED exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No

LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
TYPE OF CONTROL GEAR	Electronic transformer
LIGHT OUTLET	Direct
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
SURFACE PROTECTION HOUSING	Powder coating
TYPE OF GRID	None
LIGHT DISTRIBUTOR	None
BEAM ANGLE	Extreme wide beam >80°