

PRODUCT NO. 3620-399120

DOTLUX LED luminaire LUNAexit IP44 Ø330mm 18W COLORselect



to the product page

- Integrated single battery module with automatic self-test function
- 3h light duration with modern LI-ION
- Shadow-free light distribution with very stable PMMA cover IK07
- Constant light output due to large area aluminum core board
- Easy installation thanks to through-wireable luminaire terminal block
- Sustainable, repairable product design

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3620-0FW180 3620-1FW180 3620-2FW180
WEIGHT IN KG	0.69
POWER CONSUMPTION IN WATTS	18
NET LUMINOUS FLUX IN LUMENS	2160/2200/2180
LUMEN PER WATT	120/122/121

Dimensions

diameter: 330mm
height: 95mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP44
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
IK PROTECTION	IK07
BATTERY RUNTIME	3h
LUMEN PER WATT	120/122/121
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
PICTOGRAM INCLUDED	No
SWITCH CYCLES	> 100.000
INSTALLATION OPENING DIAMETER IN MM	0
INPUT VOLTAGE SPAN	240
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	240
SELF-TEST	Automatic self-test
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001957

WITH ILLUMINANT	Yes
LAMP HOLDER	without
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK07
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
CONNECTION TYPE	Push-in clamp
EXCHANGEABLE CONTROL GEAR	Yes
LAMP TYPE	LED
MOUNTING METHOD	Ceiling mounting
WITH REMOTE CONTROL	No
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
TYPE OF CONTROL GEAR	Electronic transformer
LIGHT DISTRIBUTOR	None
MATERIAL COVER	Other