

PRODUCT NO. 3671-499120

DOTLUX LED luminaire LUNAsilver-exit Ø490mm 33W COLORselect IP44



to the product page

- 1. Decorative ring made of high quality brushed aluminum
- 2. Cozy atmosphere due to indirect light components
- 3. Shadow-free light distribution with very stable PMMA cover IK07
- 4. Constant light output due to large-area aluminum core board
- 5. Easy installation, thanks to through-wireable luminaire terminal block
- 6. Sustainable, repairable product design

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3671-399160
WEIGHT IN KG	1.5
NET LUMINOUS FLUX IN LUMENS	3240/3730/3620
POWER CONSUMPTION IN WATTS	33
LUMEN PER WATT	98/113/110

Dimensions

diameter: 490mm
height: 115mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP44
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
RANGE OF SENSOR	0
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
IK PROTECTION	IK06
BATTERY RUNTIME	3h
LUMEN PER WATT	98/113/110
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
PICTOGRAM INCLUDED	No
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	0
INSTALLATION OPENING LENGHT IN MM	0
INPUT VOLTAGE SPAN	186-240
WARRANTY IN YEARS	5
L80/B10	50000
RATED CURRENT	0.17
DIMMING WITHOUT DIMMER	No
ENABLED LICENSED PRODUCT	Yes

INPUT VOLTAGE RANGE LUMINAIRE	186-240
SELF-TEST	Automatic self-test
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
LIFETIME L80/B20 AT 25°C	0
ETIM GRUPPEN-ID	EC001957
WITH ILLUMINANT	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	0
LAMP HOLDER	without
TYPE OF CONTROL GEAR	LED operating device current- controlled
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
CONNECTION TYPE	Push-in clamp
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED
MOUNTING METHOD	Ceiling mounting
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
LIFETIME L90/B50 AT 25°C	33333
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
LIGHT DISTRIBUTOR	None
MATERIAL COVER	Other