


PRODUCT NO. 5452

**DOTLUX Long range remote control for LED damp-proof luminaire MISTRALsensor IP66 1540mm 39W 4000K frosted with radar sensor (2822-840120/2822-940120)**



to the product page



Remote control with increased range for setting the sensor functions of the MISTRALsensor

Suitable for light point height from 4m

One remote control can be used for any number of MISTRALsensor luminaires.

The remote control must be pointed at the luminaire to change settings.

The following values are adjustable in steps:

- Range range via dip switch 5m/10m/15m
- Daylight sensor (5 / 15 / 30 / 50 / 100 / 150 lux deactivated)
- Light duration (5s / 30s / 1min / 3min / 5min / 10min / 20min / 30min)
- Afterglow time ( 0s / 10s/ 1min / 3min / 5min / 10min / 30min / permanent)
- Afterglow brightness (10% / 20% / 30% / 50%)
- Detection range (25% / 50% / 75% / 100%)

SUCCESION ARTICLE	-	ETIM GRUPPEN-ID	EC000678
WEIGHT IN KG	0.1	WIRELESS	Nein
		SIGNAL TRANSMISSION	Infrared
		BI-DIRECTIONAL	No
		UNI-DIRECTIONAL	Yes
		ADAPTIVE (SELF-LEARNING)	Nein
		WITH DISPLAY	No
		PRE-PROGRAMMED	Yes
		BEG FUNDING	Only relevant in Germany
Dimensions			
height:	25mm		
length:	175mm		
width:	55mm		