

PRODUCT NO. 4671-140140

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 27W 4000K IK10 DALI



to the product page

- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 5-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	-	BEAM ANGLE	140°
WEIGHT IN KG	1.67	PROTECTION CLASS (IP)	IP54
POWER CONSUMPTION IN WATTS	27	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	3650	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	135	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK10
		LUMEN PER WATT	135
		PROTECTION CLASS	I
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic matt/satinized
		DIMMING DALI	Yes
		NO DIM FUNCTION	No
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK10
		SUITABLE FOR EMERGENCY LIGHTING	Yes

Dimensions

height: 85mm
length: 1160mm
width: 109mm

COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
PULSE DURATION IN μ S	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No