

PRODUCT NO. 4672-140140

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 51W 4000K IK10 DALI



to the product page

- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 5-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components
- The large luminous surface made of polycarbonate produces a uniform and at the same time ceiling-brightening light distribution

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4672-040140
WEIGHT IN KG	2.158
NET LUMINOUS FLUX IN LUMENS	7140
LUMEN PER WATT	140
POWER CONSUMPTION IN WATTS	51

Dimensions

width: 159mm
height: 85mm
length: 1160mm

BEAM ANGLE	140°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
IK PROTECTION	IK10
LUMEN PER WATT	140
PROTECTION CLASS	I
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING DALI	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK10

COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
PULSE DURATION IN μ S	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
COLOUR OF LIGHT ADJUSTABLE	No