

PRODUCT NO. 2355-540120

DOTLUX LED moisture-proof luminaire MISTRAL IP66 1240mm max36W 4000K frosted



to the product page

- Faster installation thanks to innovative luminaire design. Combination of LED gear tray and cover.
- Individually replaceable branded components for the lowest maintenance costs
- UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- 5-pole through-wired with two internal luminaire connection terminals
- 2 full cable glands & blanking plugs
- Stainless steel fasteners with integrated anti-theft device
- Mounting accessories supplied (chain/ceiling/wall mounting) incl. rear panel punchings
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in locations with a fire hazard (DIN EN 60598-2-24, VDE 0711-2-24)
- This LED luminaire is suitable for use in food processing plants.
This means it can also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).
- Sustainable product design thanks to easily replaceable components

SUCCESSION ARTICLE	-	BEAM ANGLE	120°
PREDECESSOR ARTICLE	2355-1 2355-140180 2355-340180 2355-440120	PROTECTION CLASS (IP)	IP66
WEIGHT IN KG	1.8	LIGHT COLOR	white
LUMEN PER WATT	138/137/136/134	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	21/26/31/36	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	2900/3575/4225/4845	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		IK PROTECTION	IK08
		LUMEN PER WATT	138/137/136/134
		PROTECTION CLASS	I
		HOUSING COLOUR	gray
		SWITCH CYCLES	> 100.000
		FOOD-READY	Yes
		WARRANTY IN YEARS	5
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No

Dimensions

height: 80mm
length: 1240mm
width: 100mm

DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONNECTION TYPE	Cable
OPERATION BY BLUETOOTH	No
EXCHANGEABLE CONTROL GEAR	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
BEAM ANGLE	Extreme wide beam >80°