

PRODUCT NO. 4177-130120

DOTLUX LED downlight UNISIZE 22W 3000K



to the product page

- Surface-mounted light for all installation openings from 55-270mm
- Easy installation thanks to removable, infinitely adjustable mounting bracket with safety catch/mounting aid
- Removable spring clips allow direct screwing to walls and ceilings
- Extremely space-saving design thanks to integrated ballast
- Stable light output thanks to non-yellowing PMMA light guide

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4177-030120
WEIGHT IN KG	0.75
POWER CONSUMPTION IN WATTS	22
LUMEN PER WATT	100
NET LUMINOUS FLUX IN LUMENS	2200

Dimensions

height: 20mm
diameter: 290mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	200 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,7
INRUSH CURRENT IN A	0.53
IK PROTECTION	IK05
LUMEN PER WATT	100
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 60.000
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	55-270
INSTALLATION OPENING LENGHT IN MM	0
INPUT VOLTAGE SPAN	220
WARRANTY IN YEARS	2
L80/B10	15000
RATED CURRENT	0.1
SIMILAR TO RAL-COLOUR	9016
SUITABLE FOR SURFACE MOUNTING	Yes

SUITABLE FOR MOUNTING	Yes
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	15000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	30000
LIFETIME L80/B20 AT 25°C	0
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	other Without
MATERIAL COVER	Plastic, structured
TYPE OF CONTROL GEAR	LED operating device current- controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK05
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No

FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Through wiring included
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	22
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	30000
LIFETIME L90/B10 AT 25°C	7500
PULSE DURATION IN µs	20
LIFETIME L90/B50 AT 25°C	10000
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	96
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
REFLECTOR	White
LIGHT SHARING	Symmetric
LIGHT OUTLET	Direct/indirect
ADJUSTABILITY	Not adjustable
BEAM ANGLE	Extreme wide beam >80°
SURFACE PROTECTION	Untreated