

PRODUCT NO. 5508-060360

DOTLUX LED rescue light EXITflip with CINEMA MODE max.2,5W 6000K incl. 6 pictograms 3h operation, Li-ion battery with self-test



PROLINE



to the product page

- \"ONE FOR ALL\" One order number for all arrow directions
- Replaceable Li-ion battery guarantees a lighting time of 3 hours
- Various switching programs selectable: continuous or standby mode
- Wall/ceiling mounting with infinitely variable folding pictogram
- With the matching track adapter 5519, the EXITflip can be mounted in all 3-phase tracks
- Automatic self-test function with integrated operating status indicator LED
- Power consumption in standby mode less than 0.5 watts
- Power consumption in cinema mode less than 1 watt
- Power consumption in continuous operation less than 2.5 watts
- Includes 6 standard pictograms arrow (left, right, up, down)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.8	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	2,5	RANGE OF SENSOR	30
LUMEN PER WATT	7	COLOR TEMPERATURE IN KELVIN	6000
NET LUMINOUS FLUX IN LUMENS	18	COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,3
		LUMEN PER WATT	7
		PROTECTION CLASS	II
		HOUSING COLOUR	white
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001957
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
		MATERIAL COVER	Other

Dimensions

height: 230mm
length: 328mm
width: 43mm