

PRODUCT NO. 5509-060360

**DOTLUX LED rescue light EXITflip max.3W 6000K incl. 6 pictograms 8h operation, Li-ion battery with self-test**



to the product page

- \"ONE FOR ALL\" One order number for all arrow directions
- Replaceable Li-Ion battery guarantees a lighting time of 8 hours
- Various switching programs selectable: continuous or standby mode
- Wall/ceiling mounting with infinitely variable folding pictogram
- With the matching track adapter 5519, the EXITflip can be mounted in all 3-phase tracks
- Power consumption in standby mode less than 0.5 watts
- Power consumption in charging mode less than 3 watts
- Automatic self-test function with integrated operating status indicator LED
- Includes 6 standard pictograms arrow (left, right, up, down)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.8	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	3	RANGE OF SENSOR	30
NET LUMINOUS FLUX IN LUMENS	18	COLOR TEMPERATURE IN KELVIN	6000
LUMEN PER WATT	6	COLOR-RENDERING-INDEX	CRI > 82
		LUMEN PER WATT	6
		PROTECTION CLASS	II
		HOUSING COLOUR	white
		PICTOGRAM INCLUDED	Yes
Dimensions		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
width: 43mm		ETIM GRUPPEN-ID	EC001957
height: 230mm		BEG FUNDING	Only relevant in Germany
length: 328mm		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
		MATERIAL COVER	Other