

PRODUCT NO. 4965-030120-B-Ware

**DOTLUX LED solar wall light FLASHwall with sensor 3.5W 3000K**



to the product page

- Solar lithium-ion battery light with motion sensor (2 selectable operating modes).
- Reliable and fast battery charging due to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting thanks to warm white LEDs and motion sensor
- High-quality, splash-proof aluminium housing with weather-resistant powder coating
- Large homogeneously designed illuminated surface enables glare-free light distribution
- Easy alignment of the luminaire thanks to adjustable stainless steel mounting bracket
- Includes rechargeable battery (replaceable) and mounting accessories

Operating modes Motion sensor:

- A) 15% permanent light intensity after sunset , 100% light intensity in case of movement (duration 15 seconds)  
B) 0% light intensity after sunset, 100% light intensity on movement (duration 15 seconds)

<b>WEIGHT IN KG</b>	1.8
<b>POWER CONSUMPTION IN WATTS</b>	3.5
<b>NET LUMINOUS FLUX IN LUMENS</b>	250

**Dimensions**

**length:** 160mm  
**width:** 180mm  
**height:** 255mm

<b>BEAM ANGLE</b>	120°
<b>PROTECTION CLASS (IP)</b>	IP54
<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
<b>COLOR TEMPERATURE IN KELVIN</b>	3000
<b>COLOR-RENDERING-INDEX</b>	CRI > 82
<b>MOTION SENSOR</b>	Infrared, 6-10m, 120°
<b>INRUSH CURRENT IN A</b>	0
<b>IK PROTECTION</b>	IK06
<b>BATTERY RUNTIME</b>	3h at 100% / 20h at 15%
<b>PROTECTION CLASS</b>	III
<b>HOUSING COLOUR</b>	gray
<b>WARRANTY IN YEARS</b>	0
<b>CAPACITIY OF BATTERY IN MAH</b>	1500
<b>ASSORTMENT</b>	Proline
<b>ETIM GRUPPEN-ID</b>	EC002892
<b>IMPACT STRENGTH</b>	IK06
<b>PULSE DURATION IN µS</b>	0