

PRODUCT NO. 5529-040106

DOTLUX LED floodlight HLFsport 800W 4000K 1-10V dimmable 106°15° beam angle



to the product page

The compact HLFsport high-performance floodlight is ideal for sports fields and soccer pitches

- Optimized, asymmetrical light control enables glare-free game operation and insect protection ULR = 0 with reduced number of floodlights at the same time
- Protection of neighbors from stray light due to professional lens geometry
- Corrosion-resistant, powder-coated cast aluminum housing with pressure compensation and high IP/IK protection (IP66/IK08)
- 1-10V dimmable and therefore compatible with our radio receiver Art. 5007-1 ideal for retrofitting existing installations
- 7 years DOTLUX warranty with an above average lifetime: L80>90.000h
- Very high operational safety with integrated overvoltage protection 20kV
- This luminaire is flicker-free and therefore also suitable for high-definition (HD) television recordings
- Sustainable product design due to easily replaceable components.
- The power supply unit can be mounted directly on the floodlight or close to the ground on the pole.
- Mounting set for pole mounting Art.5531
- Other light colors can be ordered from 1pc.

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP66
WEIGHT IN KG	18.4	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	800	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	101200	SERVICE LIFE	approx. ca. 90.000 h at 25° C
LUMEN PER WATT	126	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 70
		LUMEN PER WATT	126
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	>180,000
		OVERVOLTAGE PROTECTION	20000
		INPUT VOLTAGE SPAN	176-240 V AC/DC
		WARRANTY IN YEARS	7
		INPUT VOLTAGE RANGE LUMINAIRE	176-240 V AC/DC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Glass transparent
		DIMMING 1-10 V	Yes
		NO DIM FUNCTION	No

Dimensions

length: 702mm
width: 294mm
height: 536mm

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No