

PRODUCT NO. 4865-030060

**DOTLUX LED floodlight LENSplus 100W 3000K 60° beam angle**



to the product page

Large variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass \"ULTRA CLEAR\" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy mounting without having to dismantle the bracket (freely rotatable 320°)
- Incl. 1.5m UV-stable rubber cable (H05RN-F open ends)
- Replaceable components, therefore repairable
- Sustainable product design thanks to easily replaceable components

<b>WEIGHT IN KG</b>		3.4	<b>BEAM ANGLE</b>		60°
<b>NET LUMINOUS FLUX IN LUMENS</b>		13645	<b>PROTECTION CLASS (IP)</b>		IP66
<b>POWER CONSUMPTION IN WATTS</b>		100	<b>LIGHT COLOR</b>		white
<b>LUMEN PER WATT</b>		136	<b>INPUT VOLTAGE</b>		176 - 240 V AC/DC
			<b>SERVICE LIFE</b>		approx. 50.000 h at 25°C
			<b>COLOR TEMPERATURE IN KELVIN</b>		3000
			<b>COLOR-RENDERING-INDEX</b>		CRI > 82
			<b>POWER FACTOR</b>		0,98
			<b>INRUSH CURRENT IN A</b>		0
			<b>IK PROTECTION</b>		IK08
			<b>LUMEN PER WATT</b>		136
			<b>PROTECTION CLASS</b>		I
			<b>VOLTAGE TYPE</b>		AC/DC
			<b>HOUSING COLOUR</b>		black
			<b>SUITED FOR EMERGENCY LIGHTING</b>		No
			<b>SWITCH CYCLES</b>		> 100.000
			<b>OVERVOLTAGE PROTECTION</b>		up to 10000 V
			<b>WARRANTY IN YEARS</b>		7
			<b>L80/B10</b>		50000
			<b>SUITABLE FOR SURFACE MOUNTING</b>		Yes
			<b>SUITABLE FOR MOUNTING</b>		No
			<b>DIMMING WITHOUT DIMMER</b>		No
			<b>ASSORTMENT</b>		Highline
			<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>		not required
			<b>LIFETIME L80/B10 AT 25°C</b>		50000

**Dimensions**

**length:** 335mm  
**width:** 295mm  
**height:** 71mm

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
LAMP HOLDER	-
MATERIAL COVER	Glass transparent
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Ending
BEAM ANGLE ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	Yes
SUITABLE FOR LIGHT-TRACK MOUNTING	No

SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	Yes
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	33750
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Swivelling
SURFACE PROTECTION	Powder coating
BEAM ANGLE	Wide beam 41-80°
CONNECTION TYPE	Other