

PRODUCT NO. 4930-199120

DOTLUX LED surface-mounted light SURFACEdali Ø300x62 22W 3000/4000/5700K COLORselect white



to the product page

- DALI dimmable version
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Wide range of products enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable product design thanks to easily replaceable LED module and power supply unit
- Rear and side cable entry with large cable storage space enables flexible use on site
- Ideal for residential projects thanks to impact-resistant IK10 polycarbonate housing
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor areas
- Individual light color adjustable via COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4930-0FW120
WEIGHT IN KG	1.11
POWER CONSUMPTION IN WATTS	22
NET LUMINOUS FLUX IN LUMENS	2640/2690/2670
LUMEN PER WATT	120/122/121

Dimensions

height: 62mm
diameter: 300mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	multicoloured
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK10
LUMEN PER WATT	120/122/121
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic, structured
DIMMING DALI	Yes
NO DIM FUNCTION	No
IMPACT STRENGTH	IK10
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COLOUR OF LIGHT ADJUSTABLE	Positions

BEG FUNDING

only relevant in Germany

**ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE**

D

BEAM ANGLE

Extreme wide beam >80°