

PRODUCT NO. 4936-1

DOTLUX LED power supply QUICK-FIXadapt CC 400-700mA



to the product page

Non-dimmable power supply unit for QUICK-FIXadapt with 500mA and IP40.

- incl. magnetic attachment
- Input voltage: 220-240 V AC
- Output voltage: 27 - 42 V DC
- The temperature range at which the power supply unit can be used is between -20°C and 40°C.
- The cable length of the power supply unit is 24cm.

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4936
WEIGHT IN KG	0.15
POWER CONSUMPTION IN WATTS	20

Dimensions

length: 152mm
width: 48mm
height: 43mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
OUTPUT CURRENT IN A	0,5
POWER FACTOR	0,97
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	25 - 40 DC
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany