

PRODUCT NO. 4485-299120

**DOTLUX LED surface-mounted light SURFACEsensor Ø300x62 25W 3000/4000/5700K  
COLORselect white**



to the product page

- Version with motion (radar) and daylight sensor (several lights can be programmed with one remote control, please order remote control 5713 separately)
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Wide range of products enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable product design thanks to easily replaceable LED module and power supply unit
- Rear and side cable entry with large cable storage space enables flexible use on site
- Ideal for residential projects thanks to impact-resistant IK10 polycarbonate housing
- Modern, clear housing with indirect light component
- Splash-proof design for outdoor, wet room and indoor areas
- Individual light color adjustable via COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4485-1FW120
WEIGHT IN KG	1.17
LUMEN PER WATT	120/125/122
POWER CONSUMPTION IN WATTS	21
NET LUMINOUS FLUX IN LUMENS	2540/2630/2570

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	multicoloured
INPUT VOLTAGE	186 - 240 AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK10
LUMEN PER WATT	120/125/122
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
WARRANTY IN YEARS	5
L80/B10	50000
SUITABLE FOR SURFACE MOUNTING	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes

**Dimensions**

**height:** 62mm  
**diameter:** 300mm

SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR CEILING MOUNTING	Yes
MATERIAL COVER	Plastic, structured
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK10
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	Yes
WITH LIGHT SENSOR	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
CONSTANT LIGHT OUTPUT (CLO)	No
COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
LAMP TYPE	LED
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D

**TYPE OF WIRING**

Suitable for through wiring

**BEAM ANGLE ADJUSTABLE**

No

**LIGHT OUTLET**

Direct/indirect

**BEAM ANGLE**

Extreme wide beam >80°