

PRODUCT NO. 3679-1-B-Ware

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 3h B-goods



to the product page

- Replaceable rechargeable battery with a light duration of 3 hours
- Integrated control LED for operating status
- Only suitable for standby mode. If the light is supplied with mains power, the integrated rechargeable battery charges and the light is in stand-by mode.
- Incl. two easy-to-change lenses
  - Corridor lighting (asymmetrical)
  - Wide beam
- Automatic self-test function

WEIGHT IN KG	0.41
NET LUMINOUS FLUX IN LUMENS	240
POWER CONSUMPTION IN WATTS	0,5

Dimensions

height: 62mm  
diameter: 140mm

BEAM ANGLE	180°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
POWER FACTOR	0,3
BATTERY RUNTIME	3h
PROTECTION CLASS	II
INSTALLATION OPENING DIAMETER IN MM	120
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ETIM GRUPPEN-ID	EC001957