

PRODUCT NO. 4867-150120

DOTLUX LED floodlight LENSplus 200W 5000K 120° beam angle



to the product page

Large variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass \"ULTRA CLEAR\" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy installation without having to dismantle the bracket (freely rotatable 320°)
- Easy installation thanks to cable connector
- Sustainable product design thanks to easily replaceable components

| | |
|-----------------------------|-------------|
| SUCCESSION ARTICLE | - |
| PREDECESSOR ARTICLE | 4867-050120 |
| WEIGHT IN KG | 5.5 |
| POWER CONSUMPTION IN WATTS | 200 |
| NET LUMINOUS FLUX IN LUMENS | 26700 |
| LUMEN PER WATT | 133 |

| | |
|--|--------------------------|
| BEAM ANGLE | 120° |
| PROTECTION CLASS (IP) | IP66 |
| LIGHT COLOR | white |
| INPUT VOLTAGE | 176 - 240 V AC/DC |
| SERVICE LIFE | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 5000 |
| COLOR-RENDERING-INDEX | CRI > 82 |
| POWER FACTOR | 0,98 |
| IK PROTECTION | IK08 |
| LUMEN PER WATT | 133 |
| PROTECTION CLASS | I |
| VOLTAGE TYPE | AC/DC |
| HOUSING COLOUR | black |
| SUITED FOR EMERGENCY LIGHTING | No |
| SWITCH CYCLES | > 100.000 |
| OVERVOLTAGE PROTECTION | up to 10000 V |
| WARRANTY IN YEARS | 7 |
| L80/B10 | 50000 |
| SUITABLE FOR SURFACE MOUNTING | Yes |
| SUITABLE FOR MOUNTING | No |
| DIMMING WITHOUT DIMMER | No |
| ASSORTMENT | Highline |
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| LIFETIME L80/B10 AT 25°C | 50000 |
| LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 100000 |

Dimensions

length: 435mm
width: 345mm
height: 78mm

| | |
|---|---|
| ETIM GRUPPEN-ID | EC001744 |
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WALL MOUNTING | Yes |
| SUITABLE FOR SUSPENDED MOUNTING | No |
| SUITABLE FOR CEILING MOUNTING | Yes |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | No |
| LAMP HOLDER | - |
| MATERIAL COVER | Glass transparent |
| TYPE OF CONTROL GEAR | LED operating device current- controlled |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | No |
| LIGHT DISTRIBUTOR | Focal lens |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM5 |
| IMPACT STRENGTH | IK08 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| SUITABLE FOR EMERGENCY LIGHTING | No |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| TYPE OF WIRING | Ending |
| OPERATION BY BLUETOOTH | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| SUITABLE FOR LOW VOLTAGE CABLE SYSTEM | No |
| SUITABLE FOR CLAMP-MOUNTING | Yes |
| SUITABLE FOR LIGHT-TRACK MOUNTING | No |
| SUITABLE FOR PEDESTAL/FLOOR MOUNTING | Yes |

| | |
|---|--------------------------|
| SUITABLE FOR TRAVERSE MOUNTING | Yes |
| EXCHANGEABLE CONTROL GEAR | No |
| LAMP TYPE | LED |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| SURFACE BRUSHED | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| LIFETIME L70/B50 AT 25°C | 100000 |
| LIFETIME L90/B10 AT 25°C | 25000 |
| LIFETIME L90/B50 AT 25°C | 33750 |
| BEG FUNDING | only relevant in Germany |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE | D |
| LIGHT OUTLET | Direct |
| COLOUR OF LIGHT ADJUSTABLE | No |
| LUMINOUS FLUX ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| ADJUSTABILITY | Swivelling |
| SURFACE PROTECTION | Powder coating |
| BEAM ANGLE | Extreme wide beam >80° |
| CONNECTION TYPE | Other |