

PRODUCT NO. 5398-25-B-Ware

DOTLUX LED glass tube NANOTUBE 58.8cm 9W 4000K frosted B-goods







to the product page

- Excellent durability thanks to UV-resistant, non-yellowing glass
- Glass cover enables better lighting effect
- Simple replacement of fluorescent tubes with starter
- Full, optimum light output immediately after switching on

ONLY AVAILABLE AS A PACKAGE UNIT (25 pieces)!

PREDECESSOR ARTICLE	1615-140180	BEAM ANGLE	220°
		PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	2.5	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	9	BASE	G13
NET LUMINOUS FLUX IN LUMENS	1440	COLOR TEMPERATURE IN KELVIN	4000
LUMEN PER WATT	160	COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	160
Dimensions		WARRANTY IN YEARS	0
		L80/B10	30000
length: 602mm		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	С
diameter: 28mm		LIFETIME L80/B10 AT 25°C	30000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
		ETIM GRUPPEN-ID	EC001959
		LIFETIME L70/B50 AT 25°C	50000
		PULSE DURATION IN µS	0
		LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K