

PRODUCT NO. 4177-040120-B-Ware

DOTLUX LED downlight UNISIZE 22W 4000K



to the product page

WEIGHT IN KG	0.75
POWER CONSUMPTION IN WATTS	22
NET LUMINOUS FLUX IN LUMENS	2300
LUMEN PER WATT	105

Dimensions

height: 14mm
diameter: 290mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 20.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,76
INRUSH CURRENT IN A	0
LUMEN PER WATT	105
GLARE-FREE	UGR < 25
SWITCH CYCLES	> 40.000
INSTALLATION OPENING DIAMETER IN MM	60-260
WARRANTY IN YEARS	0
SIMILAR TO RAL-COLOUR	9003
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	30000
ETIM GRUPPEN-ID	EC001744
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	30000
PULSE DURATION IN µS	0