

PRODUCT NO. 4932-OFW120-B-Ware

DOTLUX LED surface mounted luminaire SURFACEsensor-exit Ø300x62 25W 3000/4000/5700K COLORselect white



to the product page

- Additional 3h emergency light function with built-in lithium ion battery.
- Version with motion (radar) and daylight sensor (several luminaires can be programmed with one remote control, please order remote control separately)
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Large product variety enables use in all projects (e.g. sensor, Exit, DALI ...)
- Sustainable design, LED module, power supply unit and battery can be replaced without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact-resistant polycarbonate housing IK10
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor use
- Individual light colour adjustable with COLORselect (light colour: 3,000 K / 4,000 K / 5,700 K)
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light Distribution
- Flexible cable entry possible at the rear and side

WEIGHT IN KG	1.246
POWER CONSUMPTION IN WATTS	25
NET LUMINOUS FLUX IN LUMENS	2370-2600
CONSUMPTION (KWH/1000H)	25

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	multicoloured
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
OUTPUT LUMEN DURING EMERGENCY	200
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
POWER SUPPLY	Integrated
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK10
BATTERY RUNTIME	3h
MATERIAL	plastic
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
WARRANTY IN YEARS	0
POWER EMERGENCY OPERATION IN W	3
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No

Dimensions

diameter: 300mm
height: 58mm

DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK10
SUITABLE FOR EMERGENCY LIGHTING	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
OPTICS OF THE COVER	frosted