

PRODUCT NO. 5825-040120

**DOTLUX LED module QUICK-FIXdc 1430mm max.39W 1400mA (26-28V DC) 4000K**



to the product page


- Universal magnetic LED light module for professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 200 Watt LED board with lowest current consumption enables a system efficiency of 200 Lm/Watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module also possible by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 3 magnets and 75 cm long connection cable included in the scope of delivery
- Magnetic holders allow, among other things, direct screwing to the existing luminaire housing

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5043

Power consumption and net luminous flux of the module with different operating currents:

- 39W@ 1400mA = 6700lm = 172 lm/W
- 33W@ 1200mA = 5850lm = 177 lm/W
- 29W@ 1050mA = 5200lm = 179 lm/W
- 25W@ 900mA = 4500lm = 180 lm/W
- 22W@ 800mA = 4000lm = 182 lm/W
- 19W@ 700mA = 3500lm = 184 lm/W
- 14W@ 500mA = 2630lm = 188 lm/W
- 9W@ 350mA = 1800lm = 200 lm/W



SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	0.12	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	9/14/19/22/25/29/33/39	Service life	
NET LUMINOUS FLUX IN LUMENS	1800/2630/3500/4000/4500/5200/5850/6700	COLOR TEMPERATURE IN KELVIN	4000
LUMEN PER WATT	max.200	COLOR-RENDERING-INDEX	CRI > 82
		LUMEN PER WATT	max.200
		PROTECTION CLASS	II
		VOLTAGE TYPE	DC
		SWITCH CYCLES	> 200.000
		INPUT VOLTAGE SPAN	26-28V DC
		WARRANTY IN YEARS	5
		DIMMING WITHOUT DIMMER	No
		INPUT VOLTAGE RANGE LUMINAIRE	26-28V DC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	B

**Dimensions**

length: 1430mm  
width: 20mm  
height: 17mm

<b>ETIM GRUPPEN-ID</b>	EC000996
<b>NO DIM FUNCTION</b>	No
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>CONNECTION TYPE</b>	Cable
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG1
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	Yes
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	Yes
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	neutral white 3300 to 5300 K
<b>BEG FUNDING</b>	Only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	350/500/700/800/900/1050/1200/1400
<b>SHAPE</b>	Rectangular
<b>COLOUR</b>	White