

PRODUCT NO. 4311-030120-B-Ware

DOTLUX LED spotlight FLOORslim-sensor 50W 3000K with motion detector PIR



to the product page

- Waterproof reinforced housing IP 65 with efficient cooling design.
- ESG safety glass -ULTRA CLEAR- highly transparent glass for excellent light Color and improved light output
- Rugged, thick-walled die-cast aluminum housing screwed together multiple times
- Mounting bracket freely rotatable (320°)
- Incl. 1 m connection cable (open ends H05RN-F)
- At the swiveling sensor, the following values can be adjusted in steps:
 - Range (up to 8 m)
 - Daylight sensor
 - Light Duration

SUCCESSION ARTICLE	5149-030120
PREDECESSOR ARTICLE	2821-140120
WEIGHT IN KG	2.45
POWER CONSUMPTION IN WATTS	50
NET LUMINOUS FLUX IN LUMENS	5100
LUMEN PER WATT	102

Dimensions

length: 312mm
width: 279mm
height: 46mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
INPUT VOLTAGE	100 - 240 V AC
SERVICE LIFE	approx. 35.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 80
MOTION SENSOR	Infrared on/off, 8m
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	102
PROTECTION CLASS	I
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	0
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK07
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0