

PRODUCT NO. 5260-050120-B-Ware

**DOTLUX LED high bay floodlight COOLER 100W 5000K 120°beam angle**



to the product page

- Suitable for high temperature environments up to +70°C
- Cold forged heat sink with 2 times higher thermal conductivity than die casting ensures optimal heat dissipation.
- Vertical cooling fins prevent dust buildup and provide durable cooling
- Extremely robust and durable ESG real glass cover also resists oil and cleaning agents
- Pressure equalization valve extends seal life and prevents condensation inside the fixture
- Modular design for different power spectrums
- Reduced glare UGR<19 for 60° version

WEIGHT IN KG	4.06
POWER CONSUMPTION IN WATTS	100
NET LUMINOUS FLUX IN LUMENS	15300
LUMEN PER WATT	153

Dimensions

length: 435mm  
diameter: 220mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP66
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 70.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	153
PROTECTION CLASS	I
VOLTAGE TYPE	AC
HOUSING COLOUR	black
SWITCH CYCLES	> 140.000
OVERVOLTAGE PROTECTION	up to 10000 V
WARRANTY IN YEARS	0
L80/B10	100000
ASSORTMENT	Highline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	100000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	147000
ETIM GRUPPEN-ID	EC001744
IMPACT STRENGTH	IK08
LIFETIME L70/B50 AT 25°C	147000

PULSE DURATION IN  $\mu$ S

0