

PRODUCT NO. 2354-335120-B-Ware

**DOTLUX LED moisture-proof luminaire MISTRAL IP66 640mm 26W 4000K frosted**



to the product page

|                             |             |
|-----------------------------|-------------|
| PREDECESSOR ARTICLE         | 2354-240180 |
| WEIGHT IN KG                | 1.084       |
| POWER CONSUMPTION IN WATTS  | 26          |
| NET LUMINOUS FLUX IN LUMENS | 3500        |
| LUMEN PER WATT              | 135         |

**Dimensions**

length: 640mm  
width: 100mm  
height: 80mm

|                                           |                          |
|-------------------------------------------|--------------------------|
| BEAM ANGLE                                | 120°                     |
| PROTECTION CLASS (IP)                     | IP66                     |
| INPUT VOLTAGE                             | 220 - 240 V AC           |
| SERVICE LIFE                              | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN               | 4000                     |
| COLOR-RENDERING-INDEX                     | CRI > 82                 |
| POWER FACTOR                              | 0,9                      |
| INRUSH CURRENT IN A                       | 0                        |
| IK PROTECTION                             | IK08                     |
| LUMEN PER WATT                            | 135                      |
| PROTECTION CLASS                          | I                        |
| HOUSING COLOUR                            | gray                     |
| SWITCH CYCLES                             | > 100.000                |
| FOOD-READY                                | Yes                      |
| WARRANTY IN YEARS                         | 0                        |
| ASSORTMENT                                | Proline                  |
| ETIM GRUPPEN-ID                           | EC002892                 |
| DIMMING 0-10 V                            | No                       |
| DIMMING 1-10 V                            | No                       |
| DIMMING DALI                              | No                       |
| DIMMING DMX                               | No                       |
| DIMMING DSI                               | No                       |
| DIMMING POTENTIOMETER (INTEGRATED)        | No                       |
| DIMMING LINESWITCH                        | No                       |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No                       |

|                                          |      |
|------------------------------------------|------|
| <b>DIMMING MAINS VOLTAGE MODULATION</b>  | No   |
| <b>DIMMING PHASE CUT-OFF</b>             | No   |
| <b>DIMMING PROGRAMMABLE</b>              | No   |
| <b>DIMMING RF</b>                        | No   |
| <b>DIMMING SINE WAVE REDUCTION</b>       | No   |
| <b>DIMMING TOUCH AND DIM</b>             | No   |
| <b>DIMMING ZIGBEE</b>                    | No   |
| <b>DIMMING WITH PUSH-BUTTON</b>          | No   |
| <b>DIMMING DEPENDING ON CONTROL GEAR</b> | No   |
| <b>NO DIM FUNCTION</b>                   | Yes  |
| <b>IMPACT STRENGTH</b>                   | IK08 |
| <b>DIMMING DALI-2</b>                    | No   |
| <b>DIMMING PHASE CUT-ON</b>              | No   |
| <b>DIMMING GPRS</b>                      | No   |
| <b>PULSE DURATION IN µS</b>              | 0    |