

PRODUCT NO. 5871-030090

DOTLUX LED luminaire insert LINEAtrack 1500mm 39-63W 3000K black 90°



to the product page

- Highly efficient LINEAtrack LED luminaire insert with CRI>92 has 147 Lm/Watt
- Fastest mounting thanks to integrated track adapter
- Environmentally friendly continued use of your existing trunking system
- Flexible phase selection and power adjustment directly in the luminaire
- Long service life thanks to oversized cooling and decoupled, replaceable power supply unit

Adjustable output thanks to POWERselect

- 39W@5730 Lm = 147 Lm/Watt
- 47W@6730 Lm = 143 Lm/Watt
- 55W@7820 Lm = 142 Lm/Watt
- 63W@8780 Lm = 139 Lm/Watt

SUCCESSION ARTICLE	-	BEAM ANGLE	90°
WEIGHT IN KG	1.199	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	39W/47W/55W/63W	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	5730/6730/7820/8780	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	147/143/142/139	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0,98
Dimensions		INRUSH CURRENT IN A	30
length: 1504mm		IK PROTECTION	IK06
width: 64mm		LUMEN PER WATT	147/143/142/139
height: 55mm		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	5
		L80/B10	0
		RATED CURRENT	0.4
		SIMILAR TO RAL-COLOUR	9011
		SUITABLE FOR SURFACE MOUNTING	No
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	0
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	0

LIFETIME L80/B20 AT 25°C	0
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM5
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No

EXCHANGEABLE CONTROL GEAR	Yes
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	0
LIFETIME L90/B10 AT 25°C	0
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	Matt
LIGHT SHARING	Symmetric/asymmetric
SURFACE PROTECTION HOUSING	Powder coating
BEAM ANGLE	Variable beam angle