

PRODUCT NO. 5917-030120

DOTLUX Wall light MORPHO 6W 3000K black



to the product page

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Robust, splash-proof aluminum housing offers the best protection for outdoor use with IP65 certification
- Excellent heat management thanks to the aluminum housing ensures a long service life

SUCCESSION ARTICLE	-	BEAM ANGLE	120°
WEIGHT IN KG	0.69	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	6	LIGHT COLOR	white
LUMEN PER WATT	53	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	322	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 80
		POWER FACTOR	0,85
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK05
		LUMEN PER WATT	53
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		WARRANTY IN YEARS	3
		L80/B10	55000
		SIMILAR TO RAL-COLOUR	9005
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	55000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	82500
		ETIM GRUPPEN-ID	EC002892
		SUITABLE FOR WALL MOUNTING	Yes
		MATERIAL COVER	Plastic, transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No

Dimensions

length: 200mm
width: 100mm
height: 80mm

DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK05
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	82500
LIFETIME L90/B10 AT 25°C	27500
PULSE DURATION IN µs	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE	Extreme wide beam >80°