

PRODUCT NO. 5918-030120

**DOTLUX Wall light MORPHO 6W 3000K white**



to the product page

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Robust, splash-proof aluminum housing offers the best protection for outdoor use with IP65 certification
- Excellent heat management thanks to the aluminum housing ensures a long service life

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.69
POWER CONSUMPTION IN WATTS	6
NET LUMINOUS FLUX IN LUMENS	322
LUMEN PER WATT	53

**Dimensions**

length: 200mm  
width: 100mm  
height: 80mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 80
POWER FACTOR	0,85
INRUSH CURRENT IN A	0
IK PROTECTION	IK05
LUMEN PER WATT	53
PROTECTION CLASS	I
VOLTAGE TYPE	AC
HOUSING COLOUR	white
WARRANTY IN YEARS	3
L80/B10	55000
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	55000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	82500
ETIM GRUPPEN-ID	EC002892
SUITABLE FOR WALL MOUNTING	Yes
MATERIAL COVER	Plastic, transparent
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No

<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>IMPACT STRENGTH</b>	IK05
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	750 °C - 30 s
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	82500
<b>LIFETIME L90/B10 AT 25°C</b>	27500
<b>PULSE DURATION IN µs</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	G
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE</b>	Extreme wide beam >80°