

PRODUCT NO. 4468-299120-B-Ware

DOTLUX LED-Aufbauleuchte PANELbig 400x400mm 32W COLORselect mit 4poligem Stecker für HCL



to the product page

- One part number - three light colors adjustable through COLORselect
- Even faster installation due to specially developed base plate with pre-mounted power supply unit
- Solid, powder-coated metal housing
- Larger light area due to thinner frame
- Fatigue-free work due to flicker-free light
- Connection via quick-connect terminal
- Suitable for HCL (HCL power supply and control unit required)

SUCCESSION ARTICLE 5793-099090
PREDECESSOR ARTICLE 4468-0FW120, 4468-1FW120

WEIGHT IN KG 2.65
POWER CONSUMPTION IN WATTS max. 32
NET LUMINOUS FLUX IN LUMENS 2550 / 2800 / 2750
LUMEN PER WATT max. 88

Dimensions

length: 400mm
width: 400mm
height: 48mm

BEAM ANGLE 120°
PROTECTION CLASS (IP) IP40
LIGHT COLOR multicoloured
INPUT VOLTAGE 220 - 240 V AC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 3000/4000/5700
COLOR-RENDERING-INDEX CRI > 92
POWER FACTOR 0,98
INRUSH CURRENT IN A 0
LUMEN PER WATT max. 88
PROTECTION CLASS II
VOLTAGE TYPE AC
HOUSING COLOUR white
SWITCH CYCLES > 100.000
FOOD-READY Yes
INPUT VOLTAGE SPAN 220-240 V AC
WARRANTY IN YEARS 0
L80/B10 50000
RATED CURRENT 0.95
INPUT VOLTAGE RANGE LUMINAIRE 220-240 V AC
LIFETIME L80/B10 AT 25°C 50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 75000
ETIM GRUPPEN-ID EC002892
DIMMING 0-10 V No
DIMMING 1-10 V No

DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	75000
PULSE DURATION IN µs	0
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
SURFACE PROTECTION HOUSING	Other