

PRODUCT NO. 5992-030030

**DOTLUX Wall light Sixfold 6W 3000K white**



to the product page

This DOTLUX outdoor wall light is equipped with 6 light outlets (3 at the top and 3 at the bottom) to create an impressive play of light. With its asymmetrical lens, it provides particularly uniform and targeted illumination.

The DOTLUX Sixfold is ideal for accent lighting and creates a pleasant atmosphere.

The aluminum housing is not only robust, but also aesthetically pleasing. Whether you install it on the patio or at the front door, it will immediately enhance your outdoor area.

SUCCESSION ARTICLE	-	BEAM ANGLE	30x20
WEIGHT IN KG	0.42	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	6	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	320	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	53	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 85
		POWER FACTOR	0,8
		IK PROTECTION	IK06
		LUMEN PER WATT	53
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	No
		WARRANTY IN YEARS	3
		L80/B10	60000
		SIMILAR TO RAL-COLOUR	9005
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		MOUNTING LOCATION	Indoor + covered outdoor
		LIFETIME L80/B10 AT 25°C	60000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	90000
		ETIM GRUPPEN-ID	EC002892

**Dimensions**

**length:** 165mm  
**width:** 94mm  
**height:** 51mm

WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
MATERIAL COVER	Plastic, structured
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	Yes
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No

<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	90000
<b>LIFETIME L90/B10 AT 25°C</b>	30000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	F
<b>LIGHT SHARING</b>	Asymmetric
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT OUTLET</b>	Direct/indirect
<b>BEAM ANGLE</b>	Medium beam 21-40°
<b>SURFACE PROTECTION HOUSING</b>	Other
<b>TYPE OF CONTROL GEAR</b>	Not required
<b>DEGREE OF PROTECTION (NEMA)</b>	Other