

PRODUCT NO. 6014-040140

DOTLUX LED EX protective light MISTRALex Exit IP66 1572mm 54W 4000K IK10 Zone 2 & 22



to the product page

- UV-stable, shatterproof IK10/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- Emergency version with 3-hour rechargeable battery for emergency lighting
- Stainless steel catches with integrated anti-theft device
- Can be wired through with an internal 3-pole luminaire connection terminal
- Now supplied with two ATEX cable glands (incl. one dummy plug)
- Silicone-free, also for paint shops
- Suitable for central battery
- ATEX certified
- Explosion group:
 - II 3 G Ex ec IIC T6 Gc
 - II 3 D Ex tc IIIC T85°C Dc IP66
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in flammable locations (DIN EN 60598-2-24, VDE 0711-2-24)
- Sustainable product design thanks to easily replaceable components

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP66
WEIGHT IN KG	4.325	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	8310	COLOR TEMPERATURE IN KELVIN	4000
LUMEN PER WATT	154	IK PROTECTION	IK10
POWER CONSUMPTION IN WATTS	54	LUMEN PER WATT	154
		PROTECTION CLASS	I
		SUITED FOR EMERGENCY LIGHTING	yes
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
Dimensions		ETIM GRUPPEN-ID	EC000981
width: 145mm		WITH ILLUMINANT	Yes
height: 111mm		IMPACT STRENGTH	IK10
length: 1572mm		SUITABLE FOR EMERGENCY LIGHTING	Yes
		CONNECTION TYPE	Cable
		EXCHANGEABLE CONTROL GEAR	Yes
		SUITABLE FOR LAMP POWER IN W	54
		LAMP TYPE	LED
		MOUNTING METHOD	Wall/ceiling mounting
		BEG FUNDING	only relevant in Germany