

PRODUCT NO. 6015-040140

DOTLUX LED EX protective light MISTRALex Exit IP66 1572mm 54W 4000K IK10 Zone 2 & 22 DALI



to the product page

- UV-stable, shatterproof IK10/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- Stainless steel fasteners with integrated anti-theft device
- Emergency version with 3-hour rechargeable battery for emergency lighting
- Can be wired through with an internal 3-pole luminaire connection terminal
- Now supplied with two ATEX cable glands (incl. one dummy plug)
- Silicone-free, also for paint shops
- Suitable for central battery
- ATEX certified
- Explosion group:
 - II 3 G Ex ec IIC T6 Gc
 - II 3 D Ex tc IIIC T85°C Dc IP66
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in flammable locations (DIN EN 60598-2-24, VDE 0711-2-24)
- Sustainable product design thanks to easily replaceable components

SUCCESSION ARTICLE	-
WEIGHT IN KG	3.7
LUMEN PER WATT	154
POWER CONSUMPTION IN WATTS	54
NET LUMINOUS FLUX IN LUMENS	8310

PROTECTION CLASS (IP)	IP66
LIGHT COLOR	white
COLOR TEMPERATURE IN KELVIN	4000
IK PROTECTION	IK10
LUMEN PER WATT	154
PROTECTION CLASS	I
SUITED FOR EMERGENCY LIGHTING	yes
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING LENGHT IN MM	0
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC000981
WITH ILLUMINANT	Yes
IMPACT STRENGTH	IK10
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONNECTION TYPE	Cable
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	54
LAMP TYPE	LED
MOUNTING METHOD	Wandmontage
LIFETIME L90/B10 AT 25°C	50000
BEG FUNDING	only relevant in Germany
TYPE OF WIRING	Suitable for through wiring

Dimensions

height: 111mm
length: 1572mm
width: 145mm