

PRODUCT NO. 6074

LED power supply CC for QUICK-FIXdc 2-50W 100-1400mA 20-54V DALI dimmable NFC linear adjustable current 350mA-1050mA by dip switch



to the product page

- DALI-2 certified LED driver, 1-100% dimming range
- SELV output protection for safety and flexibility in luminaires
- Amplitude dimming for highest quality light output, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Suitable for use in emergency lighting applications
- Ideal solution for Class I and Class II

Settings selectable by dip switch: 350/400/500/600/700/800/900/1050mA

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.24	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	6-50	Output current in A	
		POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		PROTECTION CLASS	II
Dimensions		OVERVOLTAGE PROTECTION	1000 V
length: 360mm		OUTPUT VOLTAGE	20 - 54 DC
width: 30mm		INPUT VOLTAGE SPAN	198-264 V AC
height: 21mm		WARRANTY IN YEARS	5
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
		ETIM GRUPPEN-ID	EC002710
		DIMMING DALI	Yes
		NO DIM FUNCTION	No
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany