

PRODUCT NO. 5124-1

CASAMBI Gateway for up to 2 networks



to the product page

- Hardware gateway for convenient operation of up to 2 Casambi networks
- Programming of the gateway and sites functionality in the Casambi app
- Remote access via Ethernet or WIFI
- The gateway can be used for remote diagnostics, network monitoring or remote control
- Range max. 30m in free field
- HDMI cable and power supply included in the scope of delivery
- USB mouse for easy commissioning
- External LTE antenna

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE ohne 5.Ghz

WEIGHT IN KG 0.52

Dimensions

length: 108mm
width: 104mm
height: 28mm

PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 220 - 240 V AC
VOLTAGE TYPE AC
INPUT VOLTAGE SPAN 100-240 V AC
INPUT VOLTAGE RANGE LUMINAIRE 100-240 V AC
ETIM GRUPPEN-ID EC001099
MODEL Multiple interfaces
BUS SYSTEM RADIO BUS No
BUS SYSTEM KNX No
BUS SYSTEM KNX-RF (FUNK) No
BUS SYSTEM LON No
BUS SYSTEM POWERNET No
BEG FUNDING Only relevant in Germany
MOUNTING METHOD Other