

PRODUCT NO. 5037-130120

**DOTLUX Wall light BEAMO 10W 3000K anthracite**



to the product page

- Robust, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform enables quick and easy installation
- Two independently adjustable beam angles with angle indicators
- The special light diffuser enables sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting thanks to warm white LEDs and asymmetrical light distribution

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	5037-030120
WEIGHT IN KG	0.49
NET LUMINOUS FLUX IN LUMENS	900
POWER CONSUMPTION IN WATTS	10
LUMEN PER WATT	90

**Dimensions**

**width:** 97mm  
**height:** 100mm  
**length:** 120mm

BEAM ANGLE	15-120°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	yellow
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	other
LUMEN PER WATT	90
PROTECTION CLASS	I
VOLTAGE TYPE	AC
HOUSING COLOUR	anthracite
SUITED FOR EMERGENCY LIGHTING	No
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	0
INSTALLATION OPENING LENGHT IN MM	0
INPUT VOLTAGE SPAN	220-240
WARRANTY IN YEARS	3
L80/B10	50000
SUITABLE FOR SURFACE MOUNTING	Yes
SUITABLE FOR MOUNTING	No
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE RANGE LUMINAIRE	220-240

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	0
MATERIAL COVER	Plastic, transparent
TYPE OF CONTROL GEAR	-
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM2
DEGREE OF PROTECTION (NEMA)	4
IMPACT STRENGTH	other
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
WITH AIR SLOTS	Yes
FILAMENT TEST ACCORDING TO IEC 60695-2-11	-
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	-
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	10
LAMP TYPE	LED

<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>TYPE OF GRID</b>	Matt
<b>LIGHT OUTLET</b>	Direct/indirect
<b>BEAM ANGLE ADJUSTABLE</b>	Continuously variable
<b>LIGHT SHARING</b>	Symmetric/asymmetric
<b>SURFACE PROTECTION HOUSING</b>	Powder coating
<b>LIGHT DISTRIBUTOR</b>	None
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	Other
<b>BEAM ANGLE</b>	Variable beam angle
<b>CONNECTION TYPE</b>	Other
<b>LAMP HOLDER</b>	Other