

PRODUCT NO. 5187-130120

## DOTLUX LED exchangeable module QUICK-FIX24V 500x20mm 15,5W 3000K PU=12 pieces



to the product page

- Universal LED module (24V constant voltage) for quick and easy replacement of almost all light sources in existing ceiling and wall luminaires
- Simple wiring with full flexibility thanks to integrated constant current drivers. The module only needs to be supplied with 24V DC.
- Secure hold of the module thanks to 2 pre-installed neodymium magnets
- Through-wired spring pressure connection terminals at both ends
- Dimmable via our 24V PWM power supply units, e.g. also DALI
- Set consisting of 12 LED modules incl. 20 matching connectors
- Up to 4 light modules of 20W each can be operated in series connection
- Can be cut to length individually every 10cm (2 mounting holes and additional soldering surfaces per 10cm)
- In addition, 10 mounting holes are available per 50cm module for alternative fastening
- Cable can be used for single-wire wiring (rigid conductors 0.5-0.75mm<sup>2</sup>)
- Incl. release tool for releasing an already inserted cable at the plug-in terminal connection
- ESD contact protection up to 8kV for the complete module
- Can only be ordered in packaging units, not available individually
- 1 PU contains 12 pieces

SUCCESSION ARTICLE -  
PREDECESSOR ARTICLE 5187-030120

WEIGHT IN KG 0.5  
POWER CONSUMPTION IN WATTS 15,5  
NET LUMINOUS FLUX IN LUMENS 2800  
LUMEN PER WATT 181

### Dimensions

length: 500mm  
width: 20mm  
height: 15mm

BEAM ANGLE 120°  
PROTECTION CLASS (IP) IP20  
COLOR TEMPERATURE IN KELVIN 3000  
COLOR-RENDERING-INDEX CRI > 82  
POWER FACTOR 1  
SEVERABLE BY MM 100  
TC TEMPERATURE IN °C 85  
LUMEN PER WATT 181  
VOLTAGE TYPE DC  
SWITCH CYCLES > 60.000  
INPUT VOLTAGE SPAN 22-29V / DC  
WARRANTY IN YEARS 3  
L80/B10 50000  
DIMMING WITHOUT DIMMER No  
ENABLED LICENSED PRODUCT Yes  
INPUT VOLTAGE RANGE LUMINAIRE 22-29 V / DC  
ASSORTMENT Proline  
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 B  
LIFETIME L80/B10 AT 25°C 50000  
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 100000  
ETIM GRUPPEN-ID EC000996

<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM3
<b>CONNECTION TYPE</b>	Push-in clamp
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG0
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	Yes
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	Yes
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	No
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	warm white <3300 K
<b>LIFETIME L90/B50 AT 25°C</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	600
<b>SHAPE</b>	Other
<b>COLOUR</b>	White