

PRODUCT NO. 6212-030170

**DOTLUX LED exchangeable module QUICK-FIXtwilight 3W 3000K Daylight sensor**



to the product page


- Universal MAGNET LED module with integrated driver and daylight sensor for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 125lm/W thanks to low-current LEDs and therefore long service life
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 400mm

Different operating modes of the Twilight module:

1. continuous \"ON\" without daylight sensor
2. daylight sensor activated:

Light ON switching threshold approx. 20 LUX

Light OFF switching threshold approx. 40 LUX



SUCCESION ARTICLE	-
WEIGHT IN KG	0.1
POWER CONSUMPTION IN WATTS	3
NET LUMINOUS FLUX IN LUMENS	375
LUMEN PER WATT	125

**Dimensions**

**height:** 35mm  
**diameter:** 120mm

BEAM ANGLE	170
PROTECTION CLASS (IP)	IP40
INPUT VOLTAGE	186 - 240 AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,5
LUMEN PER WATT	125
PROTECTION CLASS	II
VOLTAGE TYPE	AC
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	186-240 V AC/DC
WARRANTY IN YEARS	3
L80/B10	50000
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	186-240 V AC/DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	E
MOUNTING LOCATION	Indoor + Outdoor
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
LIFETIME L80/B20 AT 25°C	0
ETIM GRUPPEN-ID	EC000996
NO DIM FUNCTION	Yes

<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM5
<b>CONNECTION TYPE</b>	Cable
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG0
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	No
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	No
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	warm white <3300 K
<b>LIFETIME L90/B50 AT 25°C</b>	34000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	13
<b>SHAPE</b>	Round
<b>COLOUR</b>	White