

PRODUCT NO. 4783-040120-B-Ware

**DOTLUX LED damp-proof luminaire HIGHFORCEabs IP66/IP69 1455mm 27W 4000K IK06 2x5-pole through-wired DALI including end cap**



to the product page

- UV-stable diffuser and housing
- Chemical resistant special diffuser made of ChemRST material
- Suitable for agricultural operations
- Housing made of impact-resistant polycarbonate
- IK06 impact resistance
- Suitable for central battery
- IP66 / IP69
- Decertified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- All HIGHFORCE lights are supplied without connector plug. You can find accessories here in the store.

SUCCESSION ARTICLE	4783-140120
WEIGHT IN KG	1.8
POWER CONSUMPTION IN WATTS	27
NET LUMINOUS FLUX IN LUMENS	3570
LUMEN PER WATT	132

Dimensions

length: 1455mm  
width: 90mm  
height: 96mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	other IP66 / IP69
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
IK PROTECTION	IK06
LUMEN PER WATT	132
PROTECTION CLASS	I
HOUSING COLOUR	gray
FOOD-READY	Yes
WARRANTY IN YEARS	0
ASSORTMENT	Highline
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
DIMMING DALI-2	Yes
PULSE DURATION IN µS	0