

PRODUCT NO. 2813-040160-NOT-B-Ware

DOTLUX LED-Lichtbandsystem LINEAclick 50W 4000K breitstrahlend dimmbar DALI Made in Germany inkl. Notstromakkukit B-Ware



- Weiterverwendung Ihres vorhandenen Tragschienensystems
- Montage ohne mechanischen Eingriff in das Tragschienensystem mit hitzebeständigen Neodym
 - Magnethalterungen inkl. Fangseil
- Eigenständiges, integriertes Kabelsystem mit Schnellsteckern
- Optimierter Transmissionsgrad der patentierten LINEAclick-Linse von DOTLUX®
- Schattenfreie Lichtverteilung durch innovatives Linsendesign
- Perfekte Kühlung des LED-Moduls dank Alu-Kernplatine
- LM80 zertifizierte LEDs mit 40% Bestromung
- Geeignet für Zentralbatterie (nur DALI Artikel-Nr 2814-350045 und 2813-450160)

WEIGHT IN KG	2.2	BEAM ANGLE	160°
POWER CONSUMPTION IN WATTS	50	PROTECTION CLASS (IP)	IP20
CONSUMPTION (KWH/1000H)	50	INPUT VOLTAGE	176 - 240 V AC/DC
NET LUMINOUS FLUX IN LUMENS	8350	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	167	COLOR TEMPERATURE IN KELVIN	4000
		POWER SUPPLY	Internal
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,97
		LUMEN PER WATT	167
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		SUITED FOR EMERGENCY LIGHTING	yes
		SWITCH CYCLES	> 100.000
		COVER MATERIAL	Polycarbonate PC
		INPUT VOLTAGE SPAN	220-240 V AC
		WARRANTY IN YEARS	0
		HOUSING MATERIAL	Aluminium
		L/B VALUE	L80/B10
		SUITED FOR EMERGENCY POWER	-
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
		DIMMING DALI	Yes
		SUITABLE FOR EMERGENCY LIGHTING	Yes
		OPTICS OF THE COVER	frosted

Dimensions

length: 1530mm
width: 73mm
height: 61mm