

PRODUCT NO. 6298-057038

## DOTLUX LED recessed light SUNLIGHT 620x310mm 47W 5700K



to the product page

- Simulates natural sunlight thanks to asymmetrical light distribution
- Most natural color rendering CRI > 92 for demanding users
- High-quality, powder-coated and visually appealing metal housing
- Glare-free working thanks to UGR<19 (suitable for VDU workstations)
- Durable construction thanks to non-yellowing PMMA lenses ensures color-stable light output
- Suitable for ceiling and wall mounting
- Mounting on grid & drywall ceiling possible
- The luminaire is supplied with a power supply unit and mounting clips

SUCCESSION ARTICLE	-
WEIGHT IN KG	1.484
POWER CONSUMPTION IN WATTS	47
NET LUMINOUS FLUX IN LUMENS	2500
LUMEN PER WATT	43

### Dimensions

width: 310mm  
height: 190mm  
length: 620mm

BEAM ANGLE	38
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
COLOR TEMPERATURE IN KELVIN	5700
COLOR-RENDERING-INDEX	CRI > 90
POWER FACTOR	0,9
IK protection	
LUMEN PER WATT	43
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	No
GLARE-FREE	UGR < 19
SWITCH CYCLES	> 160.000
INSTALLATION OPENING WIDTH IN MM	290
INSTALLATION OPENING DIAMETER IN MM	-
INSTALLATION OPENING LENGHT IN MM	600
INPUT VOLTAGE SPAN	220-240
WARRANTY IN YEARS	5
L80/B10	50000
RATED CURRENT	0.25
SUITABLE FOR SURFACE MOUNTING	Yes
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE RANGE LUMINAIRE	220-240

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	Yes
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
LAMP HOLDER	-
TYPE OF CONTROL GEAR	LED operating device current- controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK02
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
CONNECTION TYPE	Plug connection
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0

<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR LAMP POWER IN W</b>	47
<b>LAMP TYPE</b>	LED
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	50000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	G
<b>LIGHT SHARING</b>	Asymmetric
<b>LIGHT OUTLET</b>	Direct
<b>TYPE OF WIRING</b>	Suitable for through wiring
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>TYPE OF GRID</b>	White
<b>SURFACE PROTECTION HOUSING</b>	Powder coating
<b>BEAM ANGLE</b>	Medium beam 21-40°
<b>MATERIAL COVER</b>	Other