

PRODUCT NO. 3670-399160-B-Ware

DOTLUX LED luminaire LUNAsilver Ø490mm 36W COLORselect IP44



to the product page

- 1. Decorative ring made of high quality brushed aluminum
- 2. Cozy atmosphere due to indirect light components
- 3. Shadow-free light distribution with very stable PMMA cover IK07
- 4. Constant light output due to large-area aluminum core board
- 5. Easy installation, thanks to through-wireable luminaire terminal block
- 6. Sustainable, repairable product design

PREDECESSOR ARTICLE	3670-1FW160 3670-2FW160
WEIGHT IN KG	1.47
POWER CONSUMPTION IN WATTS	36
NET LUMINOUS FLUX IN LUMENS	max.3500
LUMEN PER WATT	97

Dimensions

height: 115mm
diameter: 490mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP44
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,96
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	97
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	0
ASSORTMENT	Proline
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK07
SUITABLE FOR EMERGENCY LIGHTING	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany