


PRODUCT NO. 6355-12

LED power supply unit CV 12V/DC 20W 0-1.67A SELV IP20



to the product page

- Super-flat LED power supply unit
- Flicker-free design
- Output is SELV-compliant and protected against short circuit, overload and overheating.

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4249-12
WEIGHT IN KG	0.07
POWER CONSUMPTION IN WATTS	20

Dimensions

length: 121mm  
width: 45mm  
height: 16mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 35.000 h at 25°C
OUTPUT CURRENT IN A	0-1,67
POWER FACTOR	0,85
INRUSH CURRENT IN A	30
PROTECTION CLASS	II
OUTPUT VOLTAGE	12 DC
INPUT VOLTAGE SPAN	198-264 V AC
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No

<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>MODEL</b>	Other
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	Yes
<b>SUITABLE FOR OUTDOOR USE</b>	No
<b>SUITABLE FOR CONSTANT CURRENT</b>	No
<b>HOUSING</b>	Plastic housing
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	50
<b>BEG FUNDING</b>	Only relevant in Germany