

PRODUCT NO. 4606-040120-B-Ware

**DOTLUX LED moisture-proof luminaire MISTRALht High-Temp IP66 1524mm 65W 4000K-B-Goods**



to the product page

- UV-stable housing and impact-resistant safety glass
- Aluminum housing
- IK10 impact resistance
- Stainless steel fasteners
- Suitable for central battery
- Suitable for use at high temperatures

SUCCESSION ARTICLE	-
WEIGHT IN KG	5.7
POWER CONSUMPTION IN WATTS	65
NET LUMINOUS FLUX IN LUMENS	8100
LUMEN PER WATT	125

Dimensions

length: 1524mm  
width: 105mm  
height: 75mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP66
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000h at 65°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
LUMEN PER WATT	125
PROTECTION CLASS	I
WARRANTY IN YEARS	0
AMMONIAC RESISTANCE	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>HOUSING COLOUR</b>	silver