

PRODUCT NO. 5308-030100-B-Ware

DOTLUX Wall light FLEXOtwinsensor 16W 3000K-B-goods



to the product page

- Modern, decorative sensor wall light illuminated on both sides
- Integrated PIR sensor with adjustable light duration and brightness level
- Variable lighting effects thanks to plug-in internal templates
- Robust, splash-proof aluminum housing offers the best protection for outdoor use with IP65 rating
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal
- EasyBase platform enables quick and easy installation
- Insect-friendly lighting thanks to warm white LEDs

WEIGHT IN KG	0.79
POWER CONSUMPTION IN WATTS	16
CONSUMPTION (KWH/1000H)	16
NET LUMINOUS FLUX IN LUMENS	1250
LUMEN PER WATT	78

Dimensions

length: 165mm
width: 95mm
height: 67mm

BEAM ANGLE	100°
PROTECTION CLASS (IP)	IP65
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
POWER SUPPLY	Integrated
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK06
TC TEMPERATURE IN °C	40
LUMEN PER WATT	78
PROTECTION CLASS	I
HOUSING COLOUR	black
SWITCH CYCLES	> 100.000
COVER MATERIAL	Glass
WARRANTY IN YEARS	0
HOUSING MATERIAL	Aluminium
L/B VALUE	L70/B50
SIMILAR TO RAL-COLOUR	9005
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No

DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany