

PRODUCT NO. 5151-040120-B-Ware

DOTLUX LED spotlight FLOORslim-sensor 50W 4000K black with motion detector PIR B-goods



to the product page

- Solid, waterproof, die-cast aluminum housing with efficient cooling and high-quality powder coating from Akzo Nobel
- Reliable operation thanks to brand LEDs from LUMILEDS and capacitorless power supply unit with 2kV overvoltage protection
- ESG safety glass - ULTRA CLEAR - highly transparent glass for excellent light color and improved light output
- Curved mounting bracket enables easy installation without having to dismantle the bracket (freely rotatable 320°)
- Incl. 1m UV-stable rubber cable (H05RN-F open ends)
- The following values are infinitely adjustable on the swivel-mounted PIR sensor:
 - Range (up to 7m)
 - Daylight sensor
 - Light duration

SUCCESSION ARTICLE	-	BEAM ANGLE	120°
WEIGHT IN KG	0.85	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	50	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	5950	COLOR TEMPERATURE IN KELVIN	4000
LUMEN PER WATT	119	COLOR-RENDERING-INDEX	CRI > 82
		MOTION SENSOR	Radar on/off, 8m
		IK PROTECTION	IK08
		LUMEN PER WATT	119
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		OVERVOLTAGE PROTECTION	2000 V
		WARRANTY IN YEARS	0
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

Dimensions

length: 239mm
width: 243mm
height: 68mm

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
DREH- /SCHWENKBAR	Mounting bracket freely rotatable 320°
ADJUSTABILITY	Swivelling