

PRODUCT NO. 2419

**DOTLUX LED pendant light SLIM 30 3W 3000K**



to the product page

- Indirect ceiling lighting with an OSRAM® LED
- The CITIZEN® LED with 3-step MacAdam color sorting guarantees consistent light color even with repeat orders
- Passive die-cast aluminum heat sink
- Powder-coated aluminum housing
- Incl. white canopy and cable suspension (150 cm)

SUCCESSION ARTICLE	-
WEIGHT IN KG	1.91
POWER CONSUMPTION IN WATTS	32
NET LUMINOUS FLUX IN LUMENS	2340
LUMEN PER WATT	71

**Dimensions**

height: 400mm  
diameter: 100mm

BEAM ANGLE	40°
PROTECTION CLASS (IP)	IP20
TEMPERATURE RANGE	-40°C to +40°C
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 85
INRUSH CURRENT IN A	0
LUMEN PER WATT	71
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	100-240 V AC
WARRANTY IN YEARS	5
ROPE LENGTH	1500
SIMILAR TO RAL-COLOUR	9003
INPUT VOLTAGE RANGE LUMINAIRE	100-240 V AC
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001743
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No

<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>MATERIAL COVER</b>	Without cover