

PRODUCT NO. 1617

**DOTLUX LED tube LUMENPLUS 60cm 11W 5500K clear glass rotatable end cap**



to the product page

- **TECHNICAL ADVANTAGES**
  - Internal aluminum heat sink enables optimized thermal management
  - Polycarbonate cover with UV-protective coating (non-yellowing)
  - Future-oriented due to individually replaceable power supply units
  - Individually adjustable light beam angle due to patented end cap
  - Fail-safe because each individual LED is controlled separately
  - Suitable for central battery
- **FURTHER ADVANTAGES OF THE LUMENPLUS TUBES**
  - 5 years Dotlux warranty on driver and LEDs
  - Very easy replacement of fluorescent tubes with starter
  - Immediately the full, optimal light output after switching on
  - LM80 certified LEDs
  - This tube is VDE certified

SUCCESSION ARTICLE	-	BEAM ANGLE	120°
WEIGHT IN KG	0.16	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	11	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	1430	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	5500
		COLOR-RENDERING-INDEX	CRI > 83
		SUITED FOR EMERGENCY LIGHTING	yes
		SWITCH CYCLES	> 100.000
Dimensions		INPUT VOLTAGE SPAN	220-240 V AC
length: 600mm		WARRANTY IN YEARS	5
height: 600mm		INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
diameter: 26mm		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
		ETIM GRUPPEN-ID	EC001959
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		SUITABLE FOR EMERGENCY LIGHTING	Yes
		LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
		BEG FUNDING	Only relevant in Germany
		COLOUR	White