PRODUCT NO. 2781

DOTLUX LED-Downlight CIRCLEclick LED-Modul mit integriertem Treiber dimmbar 2700K 5,5W



to the product page

+ Optimal für gewerbliche Installationen um Wartungskosten auf ein Minimum zu reduzieren
+ Treiber und Modul je nach Variante einzeln auswechselbar
+ Wartungsfreundliche, modulare Systemkomponenten
+ Natürliches Farbempfinden dank des extra hohen CRI-Wertes
+ Flexible Installationsmöglichkeiten mit vielen Lichtvarianten

SUCCESSION ARTICLE	keiner
WEIGHT IN KG	0.087

Dimensions

height: 60mm
diameter: 56mm

BEAM ANGLE	100°
PROTECTION CLASS (IP)	IP20
TEMPERATURE RANGE	-40°C to +50°C
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2700
FREQUENCY RANGE IN HZ	50/60
POWER SUPPLY	Integrated
COLOR-RENDERING-INDEX	CRI > 92
INSTALLATION DEPTH IN MM	58
MONTAGE	only with article 2776
INRUSH CURRENT IN A	0
SWITCH CYCLES	> 80.000
INPUT VOLTAGE SPAN	180-250 V AC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	180-250 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	warm white <3300 K
DREH- /SCHWENKBAR	not swivelling
ADJUSTABILITY	Not adjustable