

PRODUCT NO. 2787

DOTLUX LED downlight CIRCLEcomfort 2700K 6,5W



to the product page

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module individually replaceable with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92
- This luminaire can be upgraded for use as emergency lighting.

(The battery kit accessories are required)

SUCCESSION ARTICLE	4972-030040
WEIGHT IN KG	0.15
POWER CONSUMPTION IN WATTS	6,5
NET LUMINOUS FLUX IN LUMENS	max. 550
LUMEN PER WATT	85

Dimensions

height: 57mm
diameter: 94mm

BEAM ANGLE	38°
PROTECTION CLASS (IP)	IP20
TEMPERATURE RANGE	-40°C to +50°C
LIGHT COLOR	white
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2700
COLOR-RENDERING-INDEX	CRI > 92
INRUSH CURRENT IN A	0
LUMEN PER WATT	85
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
INSTALLATION OPENING DIAMETER IN MM	69-88
WARRANTY IN YEARS	3
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
DREH- /SCHWENKBAR	swivelling +/-30°

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

-

COLOUR OF LIGHT ADJUSTABLE
ADJUSTABILITY

No

Swivelling