
PRODUCT NO. 2844

DOTLUX LED module ADQplus 24V 24pcs/light curtain IP65 115W per light curtain 6000K



to the product page



- Simple and solder-free installation in seconds, only at the corners of the light curtain thanks to large-area prefabricated modules
- Uniform LED spacing ensures optimum illumination of the advertising space
- Yellowing-proof water protection ensures stable light output
- High color rendering index (Ra>80)
- Separable after each light strip

SUCCESSION ARTICLE	-
WEIGHT IN KG	2.1
POWER CONSUMPTION IN WATTS	115
NET LUMINOUS FLUX IN LUMENS	11500
LUMEN PER WATT	100

Dimensions

length: 1320mm

width: 1000mm

height: 9mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
TEMPERATURE RANGE	-40°C to +40°C
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	6000
COLOR-RENDERING-INDEX	CRI > 80
LUMEN PER WATT	100
VOLTAGE TYPE	DC
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	24 V DC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	24 V DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	F
ETIM GRUPPEN-ID	EC000996
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR TRAFFIC LIGHTS	No
SUITABLE FOR CONSTANT VOLTAGE	No

SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	5625
SHAPE	Rectangular
COLOUR	White